



, , , , polarity

× EtherCAT

1 ComiIDE Main Servo



2 () ReadOne



3 Polarity ↓

[0] COMI-LX554 (EtherCAT)

Axis 0 (PANASONIC_A)

Axis 1 (PANASONIC_A)

Axis 2 (PANASONIC_A)

Category

All

Load All

Save All

Compare To File

Read All

Write 1:N

Write N:N

EEP All

Load One

Save One

Compare To Axis

Read One

Write One

EEP One

Item	Name	Minimum	Maximum	Defalut	Servo	Value	Unit
43	Polarity	0	255	0	0	0	---
44	Max profile velocity	0	4294967295	104857600	104857600	104857600	1 unit/s
45	Max motor speed	0	4294967295	6000	5000	5000	1 r/min
46	Profile velocity	0	4294967295	0	0	0	1 unit/s
47	End velocity	0	4294967295	0	0	0	1 unit/s
48	Profile acceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
49	Profile deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
50	Quick stop deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
51	Motion profile type	-32768	32767	0	983040	983040	---
52	Torque slope	0	4294967295	1000	1000	1000	0.1 %/s
53	Torque profile type	-32768	32767	0	0	0	---
54	Highest sub-index supported	2	2	2	2	2	---
55	Encoder increments	1	4294967295	1048576	1048576	1048576	(-)/(pu...
56	Motor revolutions	1	4294967295	1	1	1	(nm/p)...
60	Number of entries	2	2	2	2	2	---
61	Motor revolutions	1	4294967295	1	1	1	(-)/(r(...
62	Shaft revolutions	1	4294967295	1	1	1	(-)/(r(...
63	Highest sub-index supported	2	2	2	2	2	---
64	Feed	1	4294967295	1048576	1048576	1048576	unit

Polarity

R

V

↑

↓

4 Value

0	,	,
224	,	,

5 WriteOne

[0] COMI-LX554 (EtherCAT)

Axis 0 (PANASONIC_A)

Axis 1 (PANASONIC_A)

Axis 2 (PANASONIC_A)

Category

All

Load All

Save All

Compare To File

Read All

Write 1:N

Write N:N

EEP All

Load One

Save One

Compare To Axis

Read One

Write One

EEP One

Item	Name	Minimum	Maximum	Defalut	Servo	Value	Unit
43	Polarity	0	255	0	0	224	---
44	Max profile velocity	0	4294967295	104857600	104857600	104857600	1 unit/s
45	Max motor speed	0	4294967295	6000	5000	5000	1 r/min
46	Profile velocity	0	4294967295	0	0	0	1 unit/s
47	End velocity	0	4294967295	0	0	0	1 unit/s
48	Profile acceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
49	Profile deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
50	Quick stop deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
51	Motion profile type	-32768	32767	0	983040	983040	---
52	Torque slope	0	4294967295	1000	1000	1000	0.1 %/s
53	Torque profile type	-32768	32767	0	0	0	---
54	Highest sub-index supported	2	2	2	2	2	---
55	Encoder increments	1	4294967295	1048576	1048576	1048576	(-)/(pu...
56	Motor revolutions	1	4294967295	1	1	1	(nm/p)...
60	Number of entries	2	2	2	2	2	---
61	Motor revolutions	1	4294967295	1	1	1	(-)/(r(...
62	Shaft revolutions	1	4294967295	1	1	1	(-)/(r(...
63	Highest sub-index supported	2	2	2	2	2	---
64	Feed	1	4294967295	1048576	1048576	1048576	unit

Polarity

R

V

↑

↓

6 WriteOne

[0] COMI-LX554 (EtherCAT)

Axis 0 (PANASONIC_A)

Axis 1 (PANASONIC_A)

Axis 2 (PANASONIC_A)

Category

All

Write One

Cancel

Save the parameters of the current a

Axis	Category	Item	Name	PreValue	Value
0	Object (34)	43	Polarity	0	224

Item	Name	Minimum	Maximum	Defalut	Servo	Value	Unit
43	Polarity	0	255	0	0	224	---
44	Max profile velocity	0	4294967295	104857600	104857600	104857600	1 unit/s
45	Max motor speed	0	4294967295	6000	5000	5000	1 r/min
46	Profile velocity	0	4294967295	0	0	0	1 unit/s
47	End velocity	0	4294967295	0	0	0	1 unit/s
48	Profile acceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
49	Profile deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
50	Quick stop deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
51	Motion profile type	-32768	32767	0	983040	983040	---
52	Torque slope	0	4294967295	1000	1000	1000	0.1 %/s

Polarity

R

V

↑

↓

7 EepRom

[0] COMI-LX554 (EtherCAT)

Axis 0 (PANASONIC_A)

Axis 1 (PANASONIC_A)

Axis 2 (PANASONIC_A)

Category

All

Load All

Save All

Compare To File

Read All

Write 1:N

Write N:N

Eep All

Load One

Save One

Compare To Axis

Read One

Write One

Eep One

Item	Name	Minimum	Maximum	Defalut	Servo	Value	Unit
43	Polarity	0	255	0	224	224	---
44	Max profile velocity	0	4294967295	104857600	104857600	104857600	1 unit/s
45	Max motor speed	0	4294967295	6000	5000	5000	1 r/min
46	Profile velocity	0	4294967295	0	0	0	1 unit/s
47	End velocity	0	4294967295	0	0	0	1 unit/s
48	Profile acceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
49	Profile deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
50	Quick stop deceleration	0	4294967295	1000000	1000000	1000000	1 unit/...
51	Motion profile type	-32768	32767	0	983040	983040	---
52	Torque slope	0	4294967295	1000	1000	1000	0.1 %/s
53	Torque profile type	-32768	32767	0	0	0	---
54	Highest sub-index supported	2	2	2	2	2	---
55	Encoder increments	1	4294967295	1048576	1048576	1048576	(-)/(pu...
56	Motor revolutions	1	4294967295	1	1	1	(nm/p)...
60	Number of entries	2	2	2	2	2	---
61	Motor revolutions	1	4294967295	1	1	1	(-)/(r(...
62	Shaft revolutions	1	4294967295	1	1	1	(-)/(r(...
63	Highest sub-index supported	2	2	2	2	2	---
64	Feed	1	4294967295	1048576	1048576	1048576	unit

Polarity

R

V

↑

↓

8 Log

Clear

Log Level1 : Log only when error occurred

Find

Time	Channel	Code	Command	Info
16:32:00,425	Servo Tune	100	StateComplete	Param-loading complete
16:34:12,572	Servo Tune	100	ServoParamSet	Param-Writing(1:1) Complete
16:34:42,127	Servo Tune	100	EepOne	Write Complete

x

From:
<http://comizoa.co.kr/info/> - -

Permanent link:
http://comizoa.co.kr/info/application:comiide:tool:servotunes:60_polarity?rev=1559130851

Last update: 2019/05/29 20:54