

I/O Signals 1
Digital Input 1
Digital Output 2

PCI Pulse Signal

x PCI Pulse Type

I/O Signals

- **Input/Output Signals** for each axis
- All I/O signal are optically isolated with 2500Vrms isolation voltage
- **Command pulse output pins** : OUT and DIR.
- **Incremental encoder signals input pins** : EA and EB
- **Encoder index signal input pin** : EZ
- **Mechanical limit/switch signal input pins** : \pm EL, SD/PCS and ORG
- **Servomotor interface I/O pins** : SVON, RDY, INP, ALM and ERC
- **Position latch input pin** : LTC
- **Position compare output pin** : CMP
- **Pulsar signal input pin** : PA and PB
- Simultaneous Start/Stop signal I/O pins: STA and STP

Digital Input

- Optical Isolated Input
- Opto-isolator : TLP280-4
- Input Range : 5 to 24VDC
- Isolation : 1000V Channel to Channel
- Low Voltage Level : 0V ~ 1.5V
- High Voltage Level : 5V ~ 24V
- Input Impedance : 3.6 K Ω
- COMI-LX534 Digital Input COMI-TM402 (32 DO), COMI-TM403 (32 DI), COMI-TM404 (16/16 DI/O)

Digital Output

- Optical Isolated Output
- Output Type : Darlington TR with common ground
- Output Device : ULN2803A
- Output voltage : 5V ~ 35V
- Sink Current : Max 500 mA/Channel
- Isolation Voltage : 2500 Vrms
- Throughput : 10 KHz (0.1ms)
- Response Time : 20 μ s
- COMI-LX534 Digital Output COMI-TM402 (32 DO), COMI-TM403 (32 DI), COMI-TM404 (16/16 DI/O)

From:

<http://comizoa.co.kr/info/> - -

Permanent link:

http://comizoa.co.kr/info/doku.php?id=platform:pulse:intro:io_signals

Last update: **2024/07/08 18:23**